

About the business and what we supply

Since 1997, Kevin has supplied rural and metro Western Australia with superior quality garage doors and roller shutters. Specializing in commercial and industrial projects, our team is committed to professional service and repairs.

We supply:

- Industrial Quality Roller doors up to 5.1m x 5.1m
 - Industrial Steel Roller shutters up to 10mH x 11mW
 - Chain Operated, Motorized or Remote Control
 - Emergency Commercial & Industrial Repairs
- Service Contacts Available



Kevin Garage Doors

Do it once, do it right

Steel roller shutter



▶ Kevin Garage Doors

Address: Unit 3 48 Holder Way Malaga

Ph: 1300-888-342

Fax: 92487117

Email: kgds@bigpond.com

Web: www.kevinsgaragedoors.com.au

Tel: 1300 888 342

Door specifications

SRS100*1

Curtain

Slat 100*1 BMT / 100mm height of slat, 1mm thickness of material used

Finish Galva bond / Powder-coating can be arranged, from the standard powder-coated range

Cast iron Wind-locks can be fitted every 2nd-4th slat depending on wind loading. Standard clips are nylon.

Bottom rail, to consist of an aluminum T/Bar supplied with weather seal

*** Guides**

Wind locked and non windlocked guides, 100mm width, concrete fix / Steel fix.

*** Drum**

The curtain is supported by a robust steel tube forming a drum, inside the drum are the springs which control the rise and fall of the curtain. Drum wheels to be supported by roller bearings.

*** Motorized**

All doors to be motorized using a 240-415volt motor, sized to suit you opening. Driven through a reduction gearbox.

The motor is supplied with an emergency chain wheel in the case of a power-failure operated through a hand chain which can be operated from the ground

A control box is supplied with Up down stop operation only.

*** Electrical**

PowerPoint or isolator to be fitted 1800mm from floor level and 500mm in from opening on motor side

Motors

GfA Chain Drives (made in Germany)—for Australian balanced Roller shutter:

** Safety features:*

Protection against drive overload.

Strong Gearbox Design offers High Holding Torque and protect against gearbox failure

** Operator benefits:*

Available with digital limits

Digital limits allow adjustment of the door position from the ground
All 3-phase operators are high cycle rated

High efficiency gearbox results in low power consumption

All standard operators are protected against dust and jets of water from all directions (IP65)

light compact operator, easy to install and handle

Operator mounting hole pattern suits standard Australian mounting plates.

All 3 phase operators can be wired with or without neutral supply.

Plug and play options are available for single and 3-phase operators.

Due to the unique removable shaft, all operators are suitable for left and right hand installation, reducing your stock levels will save cost.

SPECIAL FEATURE

Pull *red* activator to deactivate motor and activate manual operation.

Hand chain can now be used to open and close door. Pull *green* activator to reengage motor and deactivate hand chain. Electrical operation is now possible.

Control Panels

The new TS—range of control panels are universal, suitable for single—and three phase operators with mechanical limits & digital limits and GfA-Variable Speed Drives.

Control Range

*** TS 959;** Push Button Control

*** TS 970;** Logic Control Panel

*** TS 971;** Logic Control Panel—
with built-in receiver for wireless safety edge and remotes

Optional extra

* Remote control

* Light curtain

* Reflector beams

* Can be interfaced with loading docks



Kevin Garage Door Services

Unit 3 48 Holder Way Malaga

Phone: 1300-888-342

Fax: 92487117

Email: kgds@bigpond.com